

PATENT SPECIFICATION

(11) 1 520 473

1 520 473

- (21) Application No. 36469/75 (22) Filed 4 Sept. 1975
- (31) Convention Application No. 49/107909U
- (32) Filed 6 Sept. 1974
- (31) Convention Application No. 49/123304U
- (32) Filed 12 Oct. 1974
- (31) Convention Application No. 50/010752U
- (32) Filed 22 Jan. 1975
- (31) Convention Application No. 50/012555U
- (32) Filed 27 Jan. 1975
- (31) Convention Application No. 50/012556U
- (32) Filed 27 Jan. 1975
- (31) Convention Application No. 50/093990U
- (32) Filed 4 July 1975 in
- (33) Japan (JP)
- (44) Complete Specification published 9 Aug. 1978
- (51) INT CL² H01P 1/20
- (52) Index at acceptance
- HIW 13B1 13B2 13Y 14C 14D 14Y 5



(54) DIELECTRIC RESONATOR AND MICROWAVE FILTER USING THE SAME

(71) We, MURATA MANUFACTURING CO., LTD., a Japanese Body Corporate, of 16, Kaiden Nishijin-cho, Nagaokakyo-shi, Kyoto-fu, Japan, do hereby declare the invention, for which we pray that a patent may be granted to us, and the method by which it is to be performed, to be particularly described in and by the following statement:—

The present invention relates to a microwave filter and, more particularly, to a microwave filter including at least one dielectric resonator.

It is known in a microwave band-pass filter utilizing one or more resonators of dielectric material, to reduce undesirable spurious responses by making a relatively large difference between the resonance frequency of the high mode and that of the fundamental or dominant mode of the resonator or resonators. In order to achieve this, various methods have heretofore been employed and, of them, one method involves the appropriate selection of the ratio between the diameter and height of the resonator employed and another method involves the reduction, by any means, of the value of Q at the high mode of resonance.

However, it has been found that the first mentioned method is merely successful in increasing the ratio of the resonance frequency at the fundamental or dominant mode relative to the resonance frequency at the high mode approximating to the dominant mode to about 1.3, a value which

is insufficient to bring about a useful reduction in the spurious responses. On the other hand, it has been found that the second mentioned method cannot be readily carried out because it is difficult to reduce the value of Q at the high mode without also causing an undesirable reduction of the value of Q at the dominant mode.

Moreover, during the manufacture of the conventional dielectric resonator filter, the dielectric resonator or resonators are housed within a shielded metal case and mounted on one interior surface of the metal case through a dielectric or electrically insulating spacer or spacers rigidly secured to said one interior surface. In this case, the dielectric resonators are secured to the corresponding spacers by the use of an adhesive or bonding material. Where the adhesive material is employed to connect the individual resonators to the corresponding spacers within the metal case, respective surfaces of the resonators and corresponding spacers must be cleaned prior to application of the adhesive material and/or the type of adhesive material to be employed must carefully be selected, or otherwise improvement as to the shockproof of the filter cannot be made. In this way, the manufacture of the conventional resonator filter is very complicated.

According to the present invention, there is provided a microwave filter comprising an electrically shielded casing, a pair of

40

45

50

55

60

65

70

terminal members extending from the outside of said casing into the interior of said casing for coupling energy to and from said interior, portions of said terminal members within said interior of said casing being spaced from each other, and at least one dielectric resonator comprising a block of dielectric material having at least one aperture formed therein, said dielectric resonator being disposed within and electrically insulated from said casing and being positioned between, and spaced from said portions of said terminal members.

Preferably means are provided for tuning the filter characteristic of the or each dielectric resonator. The or each resonator may be of any desired outer shape, and in particular embodiments to be described herein comprises a cylindrical or cubic block.

The aperture formed in the or each dielectric block may either extend completely through the thickness of the block, or terminate within, for example, substantially halfway across, the thickness of the block. Accordingly, the aperture may be a through-hole, a blind hole or a cavity of any desired sectional shape, such as a circular shape or a polygonal shape. The shape of the dielectric block and the shape and type of the aperture may be selected in any desired combination. In addition, where two or more apertures are employed in the single dielectric block, respective shapes and types of the apertures may be either identical with each other or different from each other. Furthermore, the aperture may be formed in alignment with the centre line passing through the centre of the dielectric block or the longitudinal axis of the dielectric block, or alternatively be formed in eccentric relation to said centre line or said longitudinal axis of said dielectric block.

The provision of the aperture or apertures in the dielectric block forming the resonator in the microwave filter according to the present invention, the separation between the undesirable spurious frequencies and resonance frequencies at the dominant mode may be decreased as compared with the known dielectric block without such aperture formed therein.

Some embodiments of the present invention will now be described by way of example, with reference to the accompanying drawings, in which:

Figure 1 is a perspective view of a microwave filter according to a first preferred embodiment of the present invention, which is shown with a top cover separated from a metal casing to show an arrangement of dielectric resonators;

Figure 2 is a cross sectional view, on a somewhat enlarged scale, of the microwave filter shown in Figure 1;

Figures 3 to 6 are perspective view, on an enlarged scale, of different types of dielectric resonators constructed in accordance with the teachings of the present invention;

Figure 7 is a graph illustrating performance characteristics of the dielectric resonator in relation to increase of the diameter of the aperture formed in the dielectric resonator;

Figure 8 is a graph illustrating a ratio of the resonance frequency of the dominant mode relative to the resonance frequency of a mode approximating to the high mode with respect to a ratio of the outer diameter of the resonator relative to the diameter of the aperture formed in the resonator;

Figures 9 to 11, 13 and 15 illustrate various methods of mounting the dielectric resonator on one interior surface of the metal casing;

Figure 12 illustrates a method of attaching a resonance frequency tuning member, which is applicable to the dielectric resonator mounted according to any of the methods shown in Figures 10, 11 and 15;

Figure 14 illustrates another method of attaching the resonance frequency tuning member, which is applicable to the resonator mounted according to the method shown in Figure 13;

Figure 16 is a view similar to Figure 2, illustrating the microwave filter according to a second preferred embodiment of the present invention;

Figure 17 is a view similar to Figure 2, illustrating the microwave filter according to a third preferred embodiment of the present invention;

Figure 18 is a top sectional view of the microwave filter, illustrating a method of connecting probes to respective couplers adapted to receive coaxial cables for input and output microwave lines;

Figure 19 is a top sectional view of a portion of the microwave filter, illustrating one of modified probes employed therein;

Figures 20(a) and (b) are top plan view and side sectional view, respectively, of the microwave filter, illustrating a method of mounting the probes within the metal casing;

Figures 21(a) and (b) are top plan view and side sectional view, respectively, of the microwave filter, illustrating another method of mounting the probes within the metal casing;

Figure 22 is a top sectional view of a portion of the microwave filter according to a fourth preferred embodiment of the present invention;

Figures 23 (a) to (c) illustrate equivalent circuits of the microwave filter shown in Figure 22;

Figure 24 is a top sectional view of a portion of the microwave filter according to a fifth preferred embodiment of the present invention;

Figure 25 is a graph illustrating a characteristic curve of the resonance frequency in relation to the attenuation, which is achieved by the microwave filter of Figure 1;

Figure 26 is a graph illustrating a characteristic curve of the resonance frequency in relation to the attenuation, which is achieved by the microwave filter of Figures 22 and 24.

Figure 27 is a top plan view of the microwave filter according to a sixth preferred embodiment of the present invention, which is shown with a covering removed away;

Figure 28 is a side sectional view of the microwave filter shown in Figure 27;

Figure 29 is a schematic perspective view of the microwave filter shown in Figure 28;

Figure 30 illustrates a method of connecting the microwave filter of Figures 27 to 29 to a microwave integrated circuit substrate;

Figure 31 is a top sectional view of the microwave filter according to a seventh preferred embodiment of the present invention; and

Figure 32 is a graph illustrating the performance characteristic of the microwave filter shown in Figure 31.

Before the description of the preferred embodiments proceeds, it should be noted that like parts are designated by like reference numerals throughout the accompanying drawings.

Referring first to Figures 1 and 2, a microwave bandpass filter shown comprises a substantially box-like casing 10, made of any known metallic material such as brass, which casing 10 includes top and bottom coverings 10a and 10b, a pair of opposed side walls 10c and 10d and a pair of end walls 10e and 10f. Although the walls 10c to 10f are shown as integrally formed while the top and bottom coverings 10a and 10b are adapted to be secured to top and bottom edges of these walls 10c to 10f, respectively, by the use of, for example, a plurality of set screws (not shown), the walls 10c to 10f and the bottom covering 10b may be integrally formed together by excavating, or otherwise recessing, a rigid metal block.

Within the casing 10, one or more resonators, which are shown in three in number and indicated by 11a, 11b and 11c, are mounted on the bottom covering 10b through respective supporting spacers 12a, 12b and 12c and arranged in spaced and

side-by-side relation with respect to each other in a row, said supporting spacers 12a to 12c being made of any known electrically insulating material of relatively low dielectric constant. The details of each of the resonators 11a to 11c and a method of mounting the resonators 11a to 11c on the bottom covering 10b through the respective supporting spacers 12a to 12c will subsequently be described.

One of the opposed side walls 10c is provided at respective portions adjacent the opposed ends thereof with couplers 13a and 13b for respective connection with coaxial cables for microwave input and output transmission lines (not shown). These couplers 13a and 13b have axial terminals which are electrically insulated from the metal casing 10 and which are respectively connected with rods or probes 14a and 14b made of either electrically conductive material or dielectric material. The probes 14a and 14b in the instance as shown in Figures 1 and 2 extend in parallel relation to any of the end walls 10e and 10f and respectively between the end wall 10e and the end resonator 11a and between the end wall 10f and the end resonator 11c. One of the opposed ends of each of the probes 14a and 14b, which is remote from the corresponding coupler 13a or 13b, is supported by the opposed side wall 10d by means of a mounting piece 15a or 15b made of electrically insulating material such as polytetrafluoroethylene.

The microwave filter so far shown further comprises frequency tuning screws 16a, 16b and 16c which are helically adjustably extending through the top covering 10a and terminate respectively adjacent the corresponding dielectric resonators 11a to 11c. As is well known to those skilled in the art, these tuning screws 16a to 16c are not always necessary where the microwave filter without such tuning screws is precisely constructed to meet a required performance characteristic.

With particular reference to Figure 3, there is shown the details of any of the dielectric resonators 11a, 11b and 11c. The dielectric resonator is made of a cylindrical block 100 of any known dielectric material. The cylindrical block 100 has an aperture 110 of circular contour formed in said block 100 in alignment with the longitudinal axis thereof. The aperture 110 so far as the resonator of Figure 3 is concerned is a through-hole extending completely through the thickness of the block 100. Alternatively, as shown in Figure 5, the aperture 110 may extend in offset relation to the longitudinal axis of the block 100, the advantage of which will be described later.

The block may, as indicated by 101 in Figure 4, be a cubic body, in which case the

aperture 110 may extend in the direction of thickness of said cubic block 101 through the geometrical center of said cubic body or in offset relation to said geometrical center of said cubic body.

Figure 6 illustrates the cubic block 101 having the aperture 111 of a contour similar to the shape of one four-cornered surface of said cubic block 101, which aperture 111 is shown as extending in offset relation to the geometrical center of the cubic body.

Where the microwave filter is constructed with the use of dielectric resonators of the construction shown in any of Figures 3 and 5, the dominant mode of resonance is H_{01} and, on the other hand, where the microwave filter is constructed with the use of dielectric resonators of the construction shown in any of Figures 4 and 6, the dominant mode is H_{11} . Irrespective of the type of resonator, the mode approximating to the dominant mode H_{01} or H_{11} is HE_{11} . Under the HE_{11} mode, the intensity of electric field at a position near the longitudinal axis of the dielectric resonator of the construction of any of Figures 3 and 5 and Figures 4 and 6 becomes maximum. On the other hand, under the dominant mode of H_{01} or H_{11} , the intensity of electric field at a position near the longitudinal axis of the dielectric resonator of the construction of any of Figures 3 and 5 and Figures 4 and 6 becomes substantially zero.

Accordingly, the provision of the aperture 110 or 111 in the resonator has resulted in that variation of the resonance frequency of the dominant mode is very small, but a relatively great difference can be achieved between the maximum resonance frequency of the HE_{11} mode and that of the dominant mode so that the spurious response characteristic can be improved. By way of example, the resonator made of a cylindrical block of dielectric material, 14.5 mm. in diameter and 6.7 mm. in thickness, having the aperture, 5.5 mm. in diameter, formed in alignment with the longitudinal axis of the dielectric block has exhibited that the resonance frequency at the dominant mode is 3,860 MHz and the resonance frequency at the mode approximating to the dominant mode is 6,120 MHz. On the other hand, the resonator of the substantially same size without the aperture has exhibited that the resonance frequency at the dominant mode is 3,820 MHz while that at the mode approximating to the dominant mode is 5,020 MHz.

From the foregoing comparison, it is clear that, although the resonance frequency at the dominant mode in the resonator with the aperture formed therein has shifted, to 3,860 MHz as compared with

that of 3,820 MHz at the dominant mode in the resonator without the aperture formed therein, there is a great difference in the resonance frequency at the mode approximating to the dominant mode between the resonator with the aperture and that without the aperture to an extent that the spurious response characteristic can remarkably be improved.

The advantage of the provision of the aperture in the dielectric resonator is clearly supported by the graph of Figure 7, which illustrates a ratio of the resonance frequency f_{01} at the dominant mode in the cylindrical resonator, D in diameter, without the aperture relative to the resonance frequency f_1 at the dominant mode in the cylindrical resonator, D in diameter, with the aperture and a ratio of the resonance frequency f_{02} at the mode approximating to the dominant mode in the cylindrical resonator, D in diameter, without the aperture relative to the resonance frequency f_2 at the mode approximating to the dominant mode in the cylindrical resonator, D in diameter, with the aperture, both in relation to the relative increase of the diameter Dx of the aperture. On the other hand, Figure 8 is a graph illustrating a ratio of the resonance frequency f_1 at the dominant mode relative to the resonance frequency f_2 which is achieved in the cylindrical dielectric resonator, D in diameter, in relation to the increase of the diameter Dx of the aperture formed in said dielectric resonator. These data, which have provided the basis for the graphs of Figures 7 and 8, were obtained by the measurement conducted by the use of the dielectric resonator, having a dielectric constant ϵ of 36 and 0.46 in the ratio of diameter to height, and subjected to $1/\lambda_0 \approx 0.24$, wherein t represents the distance between metallic plate members positioned respectively adjacent upper and lower surfaces of the dielectric resonator and λ_0 represents the resonance wavelength at the dominant mode.

Hereinafter, the method of mounting each of the dielectric resonators 11a to 11c will be described with reference to Figures 9 to 11, and 13. However, it should be noted that, since all of the resonators 11a to 11c are mounted in the same manner, reference will be made to only one of them, for example, the resonator 11a for the sake of brevity.

Referring first to Figure 9, the resonator 11a is mounted on the bottom covering 10b of the casing 10 through the corresponding supporting spacer 12a and secured in position by a flat-headed bolt member 17 made of electrically insulating material, which bolt members 17 extends through the aperture 110 and then through the

supporting spacer 12a and is tapped into the bottom covering 10b with the flat-headed portion thereof partially seated in the aperture 110 so that the flat surface is in flush with the uppermost surface of the resonator 11a.

Figure 10 illustrates an example wherein a mounting bolt member 18 is made of metallic material. Where the metallic bolt member 18 is employed in place of the electrically insulating bolt member 17 of Figure 9, it is necessary to isolate the dielectric resonator 11a from the bolt member 18. For this purpose, in the example shown in Figure 10, the bolt member 18 has a stud portion 18a having a diameter smaller than the diameter of the aperture 110 and is inserted through the aperture 110 in alignment with the longitudinal axis of said aperture 110 with a head portion 18b thereof seated on the uppermost surface of the resonator 11a through a spacer ring 19 made of electrically insulating material. One of the ends of the bolt member 18 opposed to the head portion 18b is tapped into the bottom covering 10b.

Where the bolt member is made of electrically insulating material, a method shown in Figure 11 can be employed. In contrast to the method shown in Figure 10, the method shown in Figure 11 does not require the use of the spacer ring which has been necessitated in the method of Figure 10 to isolate the resonator 11a from its contact to the bolt member 18 and, particularly, the head portion 18b thereof. However, the bolt member 20 used in the method of Figure 11 is combined with a nut member 21. The use of the nut member 21 in connection with the bolt member 20 is recommended to ensure a steady and rigid mounting of the resonator 11a which will otherwise be achieved with no difficulty partly because of a limited thickness of the bottom covering 10b and partly because of the difference in the type of material between the bolt member 20 and the casing 10 including the bottom covering 10b. In other words, if the bolt member 20, made of electrically insulating material such as polytetrafluoroethylene or other synthetic resin, is otherwise tapped into the metallic bottom covering 10b such as practised in the method of Figure 10, the resistance to impact and/or vibration will be lower than that achieved by the use of the nut member 21 used to fasten the bolt member 20 with the resonator 11a, spacer 12a and bottom covering 10b sandwiched between a head portion 20a and the nut member 21. A stud portion 20b of the bolt member 20 may have a diameter equal to or smaller than the diameter of the aperture 110 formed in the dielectric resonator 11a.

Figure 13 illustrates a method wherein a

mounting rod, made of either electrically insulating material or metallic material, is used to support the resonator 11a. In the method of Figure 13, while the resonator 11a is sandwiched between first and second supporting spacers 22a and 22b which may be prepared from the same material as used for the spacer 12a, the mounting rod 23 extends therethrough with both ends received in respective recesses 24a and 24b formed in the top and bottom coverings 10a and 10b. At this time, one or both of the spacers 22a and 22b serve as filler pads which fill respective spaces between the lower surface of the resonator 11a and the bottom covering 10b and between the upper surface of the resonator 11a and the top covering 10a and, therefore, at the time of completion of assembly of the microwave filter, the resonator 11a can firmly be held in position within the metallic casing 10. It is, however, to be noted that, if the rod 23 is made of metallic material, it should have a diameter smaller than the diameter of the aperture 110 in the resonator 11a and extend in alignment with the longitudinal axis of said aperture 110 in spaced relation to a cylindrical wall defining the aperture 110.

In describing the various methods of mounting the resonator 11a within the casing 10, no reference has yet been made to the associated tuning screw 16a. Even though the resonator 11a is mounted in the manner as shown in any of Figures 9 to 11, the tuning screw 16a can be employed. However, in the method of any of Figures 10 and 11, since the head portion 18a or 20a of the bolt member 18 or 20, respectively, outwardly projects from the resonator 11a towards the top covering 10a, the distance the tuning screw 16a can approach the associated resonator 11a is limited and, therefore, the frequency adjustment is limited. In order to avoid this, the tuning screw 16a may have an axially inwardly extending recess 25, as shown in Figure 12, of a size sufficient to accommodate therein the head portion 18b or 20a of the bolt member 18 or 20 as the tuning screw 16a approaches the resonator 11a.

In the case where a tuning element functionally similar to the tuning screw 16a referred to above is to be applied to the mounting method of Figure 13, a completely different arrangement is required. This is illustrated in Figure 14, reference to which will now be made.

In Figure 14, the frequency tuning element, generally indicated by 26, comprises a sleeve 27 having a threaded outer peripheral surface 27a, adjustably engaged in a correspondingly threaded hole formed in the top covering 10a, and a threaded inner surface 27b adjustably

70

75

80

85

90

95

100

105

110

115

120

125

130

receiving therein an externally threaded boss member 27 rigidly mounted on one end of the rod 23 in contact with the second spacer 22b. The other end of the rod 23 is to be understood as pressure-fitted, or otherwise secured by the use of a bonding agent, into the corresponding recess 24b (Figure 13) in the bottom covering 10b.

In the arrangement of Figure 14, it will readily be seen that, by turning the sleeve 27 in either direction about the longitudinal axis thereof, one of the opposed annular ends of said sleeve 27 can be moved towards and away from the adjacent surface of the resonator 11a without accompanying any axial movement of the boss member 28 and, therefore, the resonator 11a.

In practice, irrespective of the methods of mounting the resonator 11a on the bottom covering 10b, the use of a bonding agent is preferred to ensure a rigid connection of the dielectric resonator 11a to the spacer 12a or the spacers 22a and 22b. The bonding agent may be α -cyano acrylate.

Where the resonators 11a to 11c is of the construction such as shown in any of Figures 5 and 6, the degree of coupling of these resonators can readily and easily be carried out. This is because the position of the longitudinal axis of the aperture 110 or 111 shown in Figure 5 or 6 is in offset or eccentric relation to the geometrical center of the shape of one surface of the resonator block 100 or 101. More specifically, by turning any of the resonators 11a to 11c about the mounting member such as indicated by 17 in Figure 9, 18 in Figure 10, 20 in Figure 11 or 23 in Figure 13, the distance between the adjacent two of these resonators 11a to 11c can be adjustable and, therefore, the degree of coupling can be adjustable. Once the desired degree of coupling is attained, these resonators 11a to 11c may be held in position within the filter casing 10.

Even though the resonator block 100 or 101 shown in Figure 3 or 4 is employed for the dielectric resonators 11a to 11c, a similar adjustment as to the degree of coupling can be performed with or without coupling screws, which will now be described with reference to each of Figures 15 and 16.

In Figure 15, only two of the resonators 11a and 11b are illustrated. Each of the resonators 11a and 11b is, in the instance as shown, of the construction shown in Figure 3 and is mounted on the bottom covering 10b through the spacer 12a or 12b while a mounting member M extend through the aperture 110 and then through the corresponding spacer 12a or 12b and is subsequently tapped into the bottom

covering 10b. It is to be noted that the mounting member M may be the bolt member 18 of Figure 10 and 20 of Figure 11 or the rod 23 of Figure 13, but should be understood as having a diameter smaller than the diameter of the aperture 110.

As clearly illustrated in Figure 15, depending upon the position of the longitudinal axis of the mounting member M, which extends through the dielectric resonator 11a or 11b, relative to the longitudinal axis of the aperture 110, the minimum distance between the adjacent two resonators 11a and 11b can be varied. In this way, the degree of coupling of the resonators can be adjustable during the manufacturing process and prior to the top covering 10a being rigidly secured on the top edges of the walls 10c to 10f (Figure 1).

In the embodiment shown in Figure 16, coupling screws 29a and 29b are employed. These coupling screws 29a and 29b are adjustably extending through the top covering 10a in spaced relation to each other in such a manner that the longitudinal axis of the coupling screw 29a extends intermediately between the resonators 11a and 11b and that of the other coupling screw 29b extends intermediately between the resonators 11b and 11c.

The microwave filter according to the embodiment of Figure 16 is designed such that, by the adjustment of the coupling screws 29a and 29b, the degree of coupling at the H_{11} mode can be varied while undesirable or unnecessary modes such as HE_{11} mode can be suppressed.

The coupling screws 29a and 29b may be used together with the frequency tuning screws 16a to 16c as shown in Figure 17.

Figure 18 illustrates a manner of connection between the coaxial couplers 13a and 13b and the associated probes 14a and 14b.

With particular reference to Figure 18, the input coupler 13a is in the form of a sleeve having one end portion pressure-fitted, or otherwise firmly tapped, into the side wall 10c in electrically conductive relation with respect to the filter casing 10, and the other end portion exposed to the outside of the casing 10 for connection with a coaxial cable. The coupler sleeve 13a has a hollow in which a central electrode 30 is firmly accommodated through a spacer sleeve 31 made of electrically insulating material. The associated probe 14a has one end reduced in diameter and firmly inserted into the central electrode 30 in alignment with the longitudinal axis of said electrode 30.

The output coupler 13b is of the same construction as the input coupler 13a and, therefore, the description thereof is herein omitted for the sake of brevity.

While each of the input and output probes 14a and 14b so far described is in the form of a straight rod, a substantially intermediate portion of any of the probes may be outwardly curved in complementary relation to the sectional contour of the end resonator 11a or 11c as shown in Figure 19. In addition, the inner surface of the wall 10e or 10f adjacent the associated curved portion of any of the probes 14a and 14b is preferably inwardly rounded to accommodate that curved portion of the probe in equally spaced relation to each other.

Instead of the ends of the probes 14a and 14b adjacent the wall 10d being respectively supported by said wall 10d by means of the associated mounting pieces 15a and 15b, the probes 14a and 14b may terminate adjacent the wall 10d and be secured to corresponding spacer elements 32a and 32b which as shown in Figures 20(a) and (b) may be plates secured to the inner surfaces of the walls 10e and 10f, or, as shown in Figures 21(a) and 21(b) bars secured to the inner surface of the bottom covering 10b. It is to be noted that, in any of Figures 20(a) and (b) and 21(a) and (b), the input and output couplers 13a and 13b are shown as respectively provided in the walls 10d and 10c. This does not result in reduction of the performance of the resultant microwave filter.

In the arrangement of any of Figures 20(a) and (b) and Figures 21(a) and (b), the spacer bars 32a and 32b, made of electrically insulating material, serve as striplines.

In the foregoing various embodiments of the present invention, the resonators 11a to 11c have been described as arranged in a row extending between the end walls 10e and 10f of the filter casing 10. It has been found that, in such microwave filters, as shown in the graph of Figure 25, the amount of attenuation of frequencies higher than the center frequency f_0 tends to slowly increase as indicated by a portion A of the curve in the graph of Figure 25. In order to avoid this, various methods can be contemplated. One method is to increase the number of di-electric resonators to be used within the filter casing, but would result in increase of the overall size of the resultant filter as well as the manufacturing cost.

In order to make it possible to manufacture the bandpass filter in a minimum size and also to minimize the possible loss of insertion, an additional resonator 33 in the form of a ring resonator is utilized. The position of the ring resonator 33 may be selected as desired. However, in the embodiment shown in Figure 22, the intermediate resonator 11b

and the ring resonator 33 are positioned on respective sides with respect to the center line passing through the end resonators 11a and 11b. The ring resonator 33 is selected so as to have a resonance frequency f_1 which is higher than the center frequency f_0 .

Accordingly, with respect to a microwave signal having the center frequency f_0 , a combination of the intermediate resonator 11b and the ring resonator 33 constitutes such an equivalent circuit as shown in Figure 23(a). From the circuit of Figure 23(a), it is clear that the ring resonator 33 exhibits a property of capacitance.

With respect to a microwave signal having a frequency higher than the center frequency f_0 of the filter and lower than the resonance frequency f_1 of the ring resonator 33, it is clear from the equivalent circuit of Figure 23(b) that the resonator 11b exhibits a property of electro-inductance while the ring resonator 33 exhibits a property of capacitance. Therefore, anti-resonance occurs within the range from the center frequency f_0 to the frequency higher than the center frequency but lower than the resonance frequency f_1 , so that, as shown in the graph of Figure 26, the amount of attenuation of frequencies higher than the center frequency rapidly becomes high representing a steep curve. In other words, the shape factor can be improved.

With respect to a microwave signal having a frequency equal to the resonance frequency f_1 of the ring resonator 33, it is clear from the equivalent circuit shown in Figure 23(c) that the resonator 11b exhibits a property of electro-inductance. Although a spurious response will occur, as indicated by B in the graph of Figure 26, in relation to the signal having the frequency equal to the resonance frequency f_1 , it can be neglected if the ring resonator 33 is damped with respect to Q.

In the embodiment shown in Figure 24, there is illustrated an example wherein a conventional dielectric resonator 34 is additionally employed and positioned on one side of the row of the resonators 11a to 11c and adjacent the intermediate resonator 11b while the wall 10c of the casing 10 is modified to accommodate the additional resonator 34. With respect to the performance, even the arrangement of Figure 24 is substantially similar to that shown in Figure 22.

It is to be noted that the ring resonator 33 employed in the embodiment of Figure 22 may be replaced by either a conventional dielectric resonator or a resonator of the construction shown in any of Figures 3 to 6.

A similar description made above may equally be applicable to the resonator 34 employed in the embodiment of Figure 24. Moreover, the number of additional resonators is not limited to one such as shown in any of Figures 22 and 24, but may be two or more.

Furthermore, the number of the dielectric resonators to be contained in the filter casing 10 is not limited to three, but may be one, two or more than three depending upon the desired design of the microwave filter. In addition, the number of the aperture may not be limited to one, but may be two or more. In the case where one dielectric resonator is formed with a plurality of apertures, these aperture may be of the same or difference size and may be through-holes or cavities or a combination thereof.

The dielectric resonators 11a to 11c so far illustrated may be of the same size or of different size with respect to each other.

It is to be noted that, in the microwave filter employing two or more dielectric resonators having the respective apertures of different size while the size of the dielectric resonators is selected such that the center frequency of one dielectric resonator is equal to that of the remaining dielectric resonator, the spurious frequencies peculiar to these resonators can advantageously be separated and, therefore, the overall spurious response characteristic of the microwave filter can be improved.

The embodiment shown in Figures 27 to 30 illustrates an example of microwave filter which can readily be installed on a microwave integrated circuit substrate without the use of any coaxial transmission cables.

Referring particularly to Figures 27 to 29, a microwave filter casing comprises a substantially box-like shielding cover 50 and a container 60 adapted to be covered by the shielding cover 50. The container 60 comprises a substantially U-sectioned body 61 having a pair of opposed walls 61a and 61b and a bottom wall 61c, and a pair of end walls 62a and 62b. The end walls 62a and 62b have a width substantially equal to the interior space between the walls 61a and 61b and are held in position on respective ends of the U-sectioned body 61 so that all the elements 61a to 61c and 62a and 62b cooperate to provide the container 60 of a shape similar to a top-opened box.

The container 60, including the body 61 and the end walls 62a and 62b, is made of electrically insulating material such as polytetrafluoroethylene or any other suitable synthetic resin.

As best shown in Figs. 27 and 28, each of

the end walls 62a and 62b has a interior surface inwardly rounded, or otherwise recessed, to provide a cavity 63a and 63b for minimizing the loss of insertion which may otherwise occur in association with a corresponding oscillating probe 64a and 64b. The probes 64a and 64b extend at right angles to the plane of the bottom wall 61c and intermediately of the width of the end walls 62a and 62b and have one end received by respective portions 62c and 62d of the end walls 62a and 62b and the other end extending through respective portions opposed to the portions 62c and 62d of the end walls 62a and 62b, respectively. Said respective other ends of the probes 64a and 64b are in turn connected, or otherwise integrally formed, with input and terminal members 65a and 65b which extend in parallel relation to the plane of and in flush with the bottom wall 61c. A substantially intermediate portion of each of the probes 64a and 64b bridges over the corresponding cavity 63a and 63b.

Within the container 60 of the above construction, there is accommodated a dielectric resonator 66 of the shape as shown in Fig. 3 having an aperture 66a extending in alignment with the longitudinal axis of the resonator 66. This dielectric resonator 66 is mounted on a supporting rod 67 made of synthetic resinous material and having both ends secured to, or otherwise rigidly inserted into, the walls 61a and 61b. Mounted on the supporting rod 67 between the wall 61a and the resonator 66 and between the wall 61b and the resonator 66 are spacer sleeves 68a and 68b, made of electrically insulating material such as alumina, for holding the dielectric resonator 66 in position intermediately of the length of the rod 67 and on said rod 67.

A complete microwave filter can be assembled by covering the shielding cover 50 over the container 61, substantially as shown in Fig. 30. This complete microwave filter is, as shown in Fig. 30, placed on a microwave integrated circuit substrate 55 with the terminal members 65a and 65b held flat against and subsequently soldered, as at 56a and 56b, to respective printed wirings 57a and 57b on one surface of the substrate 55 to which they are to be electrically connected.

It is to be noted that the aperture 66a in the dielectric resonator 66 may have a diameter greater than the diameter of the supporting rod 67, in which case both end faces of the resonator 66 are preferably bonded to the associated spacer sleeves 68a and 68b thereby preventing the resonator 66 from contacting the rod 67.

While in the embodiments described above except for that shown in Figs. 27 to 130

30 the frequency adjusting or tuning means have been described as comprised of one or more tuning screws, such as indicated by 16a to 16c, or sleeve such as indicated by 26, a quite different arrangement of the tuning means is employed in the embodiment which will now be described with reference to Fig. 31.

10 A microwave filter shown in Fig. 31 comprises a shielded metallic casing 70 including a hollow body 71 of any desired sectional shape and a pair of opposed lids 72a and 72b closing the respective openings at the opposed ends of the hollow body 71.

15 A pair of terminal members which project into the interior of the casing 70 for coupling energy to and from such interior, is, for the sake of clarity, omitted from the drawing. Positioned intermediately of the length of the hollow body 70 within the hollow body 70 is a carrier 73, made of electrically insulating material, which carries a dielectric resonator 74 in position within the hollow body 71. The dielectric resonator 74 has an aperture 74a in the form of a through-hole extending in a lengthwise direction of the hollow body 71.

20 The carrier 73 may be made of a single piece of electrically insulating material having an outer contour similar to the cross sectional shape of the hollow body 71 or separate pieces of electrically insulating material. If the carrier 73 is made of separate pieces, they are secured to the inner surface of the hollow body 71 in spaced relation to each other.

25 Within the filter casing 70, a pair of frequency adjusting plate members 75a and 75b are provided on respective sides of the dielectric resonator 74. These plate members 75a and 75b are respectively formed with threaded holes 76a and 76b both in alignment with the aperture 74a in the dielectric resonator 74 carried in position within the hollow body 71.

30 Extending through the holes 76a and 76b in the plate members 75a and 75b and the aperture 74a in the dielectric resonator 74 is a tuning rod 77 having one end journaled to the lid 72a and the other end rotatably extending through the other lid 72b and formed into a tuning knob as indicated by 77a. This tuning rod is threaded at portions between the lid 72a and the resonator 74 and between the resonator 74 and the lid 72b, respectively, as indicated by 78a and 78b. Respective threads on the portions 78a and 78b of the tuning rod 77 extend in opposite relation to each other around the tuning rod 77 so that the adjustment of the tuning rod 77 in either direction about the longitudinal axis thereof results in the plate members 75a and 75b simultaneously moving in a direction close to and away

from each other with the resonator 74 stationarily positioned therebetween. 65

In order to avoid any possible fluttering of any of the plate members 75a and 75b which may otherwise occur during simultaneous movement of said members 75a and 75b, one or more guide rods, only one of which is shown by 79 in Fig. 31, may be employed. In the instance as shown, the guide rod 79 has both end secured to the lids 72a and 72b, a substantially intermediate portion thereof slidably extending through the plate member 75a, then the carrier 73 and finally the plate member 75b. 70 75

The microwave filter of the construction shown in Fig. 31 exhibits a performance curve indicated by X in the graph of Fig. 32. Also shown in this graph of Fig. 32 is a performance curve Y exhibited by a microwave filter of a construction similar to that shown in Figs. 1 and 2, but having one dielectric resonator without aperture formed therein and also having a frequency tuning means in the form of a screw, which microwave filter exhibiting the performance curve Y is now commercially available. 80 85 90

In the graph of Fig. 26, the terms "interval" represented by the axis of abscissas is intended to mean the distance between the plate members 75a and 75b in the case of the present invention and the distance between the end of the tuning screw adjacent the resonator and the latter in the case of the conventional microwave filter. From the comparison of these performance curves X and Y, it will readily be seen that, with the microwave filter of the construction shown in Fig. 31, a relatively wide range of center frequencies can be adjustable with minimum reduction of the Q value. 95 100 105

Although the present invention has been fully described by way of example in connection with the various embodiments thereof, it should be noted that various changes and modifications are apparent to those skilled in the art. By way of example, the resonator according to the present invention can be used not only in the microwave bandpass filter referred to above, but also in any other microwave filters such as microstrip filters and waveguide filters. In addition, even in the embodiment shown in any of Figs. 27 to 30 and 31, the dielectric resonator may have one or more additional apertures other than the aperture such as indicated by 66a in Figs. 27 to 29 and 74a in Fig. 31. 110 115 120

Therefore, these changes and modifications are to be understood as included within the scope of the present invention unless they depart therefrom. 125

WHAT WE CLAIM IS:—

1. A microwave filter comprising an electrically shielded casing, a pair of terminal members extending from the outside of said casing into the interior of said casing for coupling energy to and from said interior, portions of said terminal members within said interior of said casing being spaced from each other, and at least one dielectric resonator comprising a block of dielectric material having at least one aperture formed therein, said dielectric resonator being disposed within and electrically insulated from said casing and being positioned between, and spaced from said portions of said terminal members.
2. A microwave filter as claimed in Claim 1, further comprising means for tuning the filter characteristic of the dielectric resonator.
3. A microwave filter as claimed in Claim 1, including a plurality of the dielectric resonators disposed within the casing and in spaced relation to each other.
4. A microwave filter as claimed in Claim 3, further comprising means for tuning the filter characteristic of each of the dielectric resonators.
5. A microwave filter according to any preceding claim wherein the dielectric resonator, or at least one of the dielectric resonators comprises a cylindrical block having an aperture extending in alignment with the longitudinal axis of the cylindrical block.
6. A microwave filter according to any of Claims 1 to 4 wherein the dielectric resonator, or at least one of the dielectric resonators comprises a cylindrical block having an aperture extending in eccentric relation to the longitudinal axis of the cylindrical block.
7. A microwave filter according to any of Claims 1 to 4 wherein the dielectric resonator, or at least one of the dielectric resonators comprises a cubic block having an aperture extending in alignment with an axis passing through the geometrical centre of the cubic block.
8. A microwave filter according to any of Claims 1 to 4 wherein the dielectric resonator, or at least one of the dielectric resonators comprises a cubic block having an aperture extending in eccentric relation to an axis passing through the geometrical centre of the cubic block.
9. A microwave filter according to any preceding claim wherein the or each dielectric resonator is fixedly mounted to a wall of the casing with an insulating spacer member between said resonator and the wall.
10. A microwave filter according to Claim 9 wherein the or each dielectric resonator is mounted by means of a bolt passing through the, or an aperture of said resonator and through the spacer member, and secured to said wall.
11. A microwave filter according to any of Claims 1 to 8 wherein the or each dielectric resonator is fixed between a pair of parallel opposed walls of the casing, with each of a pair of insulating spacer members disposed between said resonator and a respective one of said opposed walls.
12. A microwave filter according to Claim 11 wherein the or each dielectric resonator is fixed by means of a bolt passing through the or an aperture of said resonator and through the spacer members and secured at opposite ends thereof to said opposed walls.
13. A microwave filter according to Claim 2 or Claim 4 or to any of Claims 5 to 12 when dependent on Claim 2 or Claim 4, wherein said means for tuning comprise, in respect of the or each dielectric resonator a screw threaded element which projects into the interior of said casing to terminate adjacent the respective dielectric resonator, and which is mounted to said casing to be adjustable from the outside of said casing.
14. A microwave filter, substantially as hereinbefore described, with reference to and as illustrated in any of Figures 1 to 6, 9 to 22, 24 and 27 to 31.

MURATA MANUFACTURING CO.,
LTD.,

Per: Boulton, Wade & Tennant,
34 Cursitor Street,
London EC4A 1PQ.
Chartered Patent Agents.

FIG. 1.




FIG. 3.




FIG. 4.




FIG. 2.




FIG. 5.




FIG. 6.




FIG. 7.




FIG. 8.




FIG. 9.




FIG. 11.




FIG. 10.




FIG. 12.




FIG. 13.




FIG. 14.




FIG. 15.




FIG. 16.




FIG. 17.




FIG. 18.




FIG. 20. (a)




FIG. 19.




FIG. 20. (b)




FIG. 21. (a)




FIG. 22.




FIG. 21. (b)




FIG. 23. (a)




FIG. 23. (b)




FIG. 23. (c)




FIG. 27.





FIG. 25.

FIG. 28.





FIG. 26.




FIG. 29.




FIG. 30.




FIG. 31




FIG. 32.

